

DECLARATION OF CONFORMITY

DIRECTIVE 99/5/EC

Manufacturer or
authorized representative: **MC Technologies GmbH**
Kabelkamp 2
30179 Hannover
Germany

declare on our sole responsibility that the products

GSM-R / GSM / GPRS Terminals **TRM 5-Terminal, TRM-5ext-Terminal**
- Frequency range: GSM-R, GSM 900/1800 (TRM 5-Terminal)
EGSM-R, GSM 900/1800 (TRM 5ext-Terminal)
- Transmitted power: max. 2 Watts

to which this declaration relates, are in conformity with the following standards and/or other normative documents, by specific reference to the essential requirements of Article 3 of the Directive 1999/5/EC.

Health and Safety	Art. 3.1 a:	EN 60950-1:2006+A11:2009+A1:2010+A12:2011+AC:2011 +A2:2013 EN 62311:2008
EMC	Art. 3.1 b:	EN 301 489-1 v1.9.2; EN 301 489-7 v1.3.1
RF Spectrum Efficiency	Art. 3.2:	EN 301 511 v9.0.2

We hereby declare that all essential radio tests have been carried out and that the above named products are in conformity to all the essential requirements of Directive 1999/5/EC.

The technical documentation relevant to the above named product are kept at:

MC Technologies GmbH
Kabelkamp 2
30179 Hannover
Germany

MC/TECHNOLOGIES

Kabelkamp 2 - D-30179 Hannover
Telefon +49 511 67 69 99 - 0
Telefax +49 511 67 69 99 - 150
info@mc-technologies.net

Hannover, 31.08.2016

Dr. Matthias Dämmig
Managing Director



Transition declaration of EN 60950-1

Information technology equipment - Safety - Part 1: General requirements

of Version: A12 Corrigendum 1: 2012-09
German version EN 60950-1:2006/A12:2011, Corrigendum to DIN EN 60950-1/A12
(VDE 0805-1/A12):2011-08

to Version: 2014-08
IEC 60950-1:2005, modified + Cor.:2006 + A1:2009, modified + A1:2009/Cor.:2012 +
A2:2013, modified);
German version EN 60950-1:2006 + A11:2009 + A1:2010 + A12:2011 + AC:2011 + A2:2013

We : **MC Technologies GmbH**
Kabelkamp 2
30179 Hannover
Germany

declare under our sole responsibility that the products

MC Technologies **TRM 5-Terminal, TRM-5ext-Terminal**
Suitable for the frequency range: GSM-R, GSM 900/1800 (TRM 5-Terminal)
EGSM-R, GSM 900/1800 (TRM 5ext-Terminal)
With transmitted power: max. 2 Watts

are in conformity with all requirements of the new standard version of 2014.

With respect to DIN EN 60950-1 (VDE 0805-1):2011-01, DIN EN 60950-1 Corrigendum 1 (VDE 0805-1 Corrigendum 1):2012-03, DIN EN 60950-1/A12 (VDE 0805-1/A12):2011-08 und DIN EN 60950-1/A12 Corrigendum 1 (VDE 0805-1/A12 Corrigendum 1):2012-09 the following major changes took place in version 2014-08:

- a) The specifications for moisture-proof storage, clearances in primary circuits and for connecting cables to the AC power supply circuit has been changed.
- b) The method for testing the dielectric strength and the surge test were completed.


All changes are not relevant for the products mentioned above.

The technical documentation relevant to the above named product are kept at:

MC Technologies GmbH
Kabelkamp 2
30179 Hannover
Germany

MC/TECHNOLOGIES

Kabelkamp 2 - D-30179 Hannover
Telefon +49 511 67 69 99 - 0
Telefax +49 511 67 69 99 - 150
info@mc-technologies.net



Dr. Matthias Dämmig
Managing Director

Hannover, 31.08.2016